

CLAIMS

1. A method for calibrating at least one or more amplifiers (100,200),
c h a r a c t e r i s e d i n:
 - 5 i) generating a noise signal (N_a+N_i) produced by said one or more amplifiers (100,200) when no input signal (S_i+N_i) is connected (Alt. 2) to at least one amplifier of said one or more amplifiers (100,200);
 - 10 ii) using said noise signal (N_a+N_i) as a calibrating signal for estimating a corresponding gain (G) of said one or more amplifiers (100,200) by measuring (600) at least one output of said one or more amplifiers (100,200) the amount of noise (S_{tot}) of said one or more amplifiers (100,200).
- 15 2. A method for calibrating at least one or more amplifiers (100,200) according to claim 1,
c h a r a c t e r i s e d i n t h a t f u r t h e r i s s a i d g a i n (G) adjusted in accordance with said calibrating signal.
- 20 3. A method for calibrating a receiver (1,2),
c h a r a c t e r i s e d i n:
 - 25 ii) using said noise signal (N_a+N_i) as a calibrating signal for estimating a corresponding gain (G) of said one or more amplifiers in said receiver by measuring (600) at the output of the receiver the amount of noise (S_{tot}) of said one or more amplifiers (100,200).
- 30 4. A method for calibrating a receiver according to claim 3,
c h a r a c t e r i s e d i n t h a t f u r t h e r i s s a i d g a i n (G) adjusted in accordance with said calibrating signal.

5. A calibration arrangement (1,2) comprising:
 one or more amplifiers (100,200) for amplifying a radio
 signal (S_i+N_i);
 estimating means (600) for estimating a gain (G) of said
 one or more amplifiers (100,200);
 characterised in that disconnecting said
 radio signal (S_i+N_i), while at least one amplifier of
 said one or more amplifiers (100,200) is producing a
 calibrating signal (N_a+N_i) as a reference signal into
 said estimating means (600) for estimating said gain (G)
 of said radio signal (S_i+N_i).
6. A calibration arrangement (1,2) comprising:
 one or more amplifiers (100,200) for amplifying a radio
 signal (S_i+N_i);
 estimating means (600) for estimating a gain (G) of said
 one or more amplifiers (100,200);
 characterised in that said calibration
 arrangement (1,2) further comprises:
 a switching means (10,30+100) for disconnecting said
 radio signal (S_i+N_i), while at least one amplifier of
 said one or more amplifiers (100,200) is producing a
 calibrating signal (N_a+N_i) as a reference signal into
 said estimating means (600) for estimating said gain (G)
 of said radio signal (S_i+N_i).
7. A calibration arrangement (1,2) according to any one of
 claims 5-6,
 characterised in that said calibrating
 signal is a pure noise signal (N_a+N_i) of at least one
 amplifier of said one or more amplifiers (100,200).
8. A calibration arrangement (2) according to any one of
 claims 5-7,
 characterised in that disconnecting said one
 or more amplifiers (100,200) from said radio signal
 (S_i+N_i) by disconnecting a power supply (500) from at

least one amplifier of said one or more amplifiers (100,200).

9. A calibration arrangement (2) according to any one of claims 6-7,
5 c h a r a c t e r i s e d in that said switching means (30+100) is disconnecting said one or more amplifiers (200) from said radio signal (S_i+N_i) by disconnecting a power supply (500) from at least one amplifier of said one or more amplifiers (100,200).
- 10 10. A calibration arrangement (1) according to any one of claims 5-7,
c h a r a c t e r i s e d in that disconnecting said one or more amplifiers (100,200) from said radio signal (S_i+N_i) by connecting at least one input of said one or
15 more amplifiers (100,200) to a reference potential (20).
11. A calibration arrangement (1) according to any one of claims 6-7,
c h a r a c t e r i s e d in that said switching means (10) is disconnecting said one or more amplifiers (200)
20 from said radio signal (S_i+N_i) by connecting at least one input of said one or more amplifiers (100,200) to a reference potential (20).
12. A calibration arrangement (1) according to any one of claims 10-11,
25 c h a r a c t e r i s e d in that said reference potential is a resistance (20) through ground.
13. A calibration arrangement (1,2) according to any one of claims 5-12,
c h a r a c t e r i s e d in that the calibration
30 arrangement (1,2) further comprises:
more than one amplifiers (100+200) in a chain for amplifying said received radio signal (S_i+N_i).

14. A calibration arrangement (1,2) according to any one of claims 6-7,
 characterised in that said switching means (10,30+100) is disconnecting said one or more amplifiers (100,200) from said radio signal (S_i+N_i) by disconnecting at least one input of said one or more amplifiers (100,200) which is closest to where said radio signal (S_i+N_i) is inputted.
15. A calibration arrangement (1,2) according to any one of claims 5-14,
 characterised in that said calibrating signal is a noise power (kTBF) from said one or more amplifiers (100,200) that comprises:
 a known Boltzman constant (k);
 a known bandwidth (B) of said noise power;
 a known noise figure of said noise power;
 a measured temperature (T) of said receiver.
16. A calibration arrangement (1,2) according to any one of claims 5-15,
 characterised in that an output from the last one of said one or more amplifiers (100,200) in a chain is connected to an analog-digital-converter (400) for converting analog signals into digital signals.
17. A calibration arrangement (1,2) according to claim 15,
 characterised in that said gain (G) of said radio signal (S_i+N_i) is estimated from said calibrating signal (N_a+N_i) including said noise power (kTBF) when an output signal (S_{tot}) is measured at least one output of said one or more amplifiers (100,200).
18. A calibration arrangement (1,2) according to any one of claims 5-16,
 characterised in that said gain (G) of said radio signal (S_i+N_i) is estimated from said calibrating

signal (N_a+N_i) when an output signal (S_{tot}) is measured at least one output of said one or more amplifiers (100,200).

19. A calibration arrangement (1,2) according to any one of
5 claims 15-16,
c h a r a c t e r i s e d in that said gain (G) of said
radio signal (S_i+N_i) is estimated from said calibrating
signal (N_a+N_i) when an output signal (S_{tot}) is measured
after said analog-digital-converter (400).
- 10 20. A receiver (1,2) comprising:
means (300) for receiving a radio signal (S_i+N_i);
one or more amplifiers (100,200) for amplifying said
received radio signal (S_i+N_i);
estimating means (600) for estimating a gain (G) of said
15 receiver (12);
c h a r a c t e r i s e d in that said receiver further
comprises:
a switching means (10,100) for disconnecting said
received signal (S_i+N_i), while at least one amplifier of
20 said one or more amplifiers (100,200) is producing a
calibrating signal (N_a+N_i) as a reference signal into
said estimating means (600) for estimating said gain (G)
of said radio signal (S_i+N_i).
21. A receiver (1,2) according to claim 20,
25 c h a r a c t e r i s e d in that said calibrating
signal is a pure noise signal (N_a+N_i) of at least one
amplifier of said one or more amplifiers (100,200).
22. A receiver (1) according to any one of claims 20-21,
30 c h a r a c t e r i s e d in that said switching means
(10) is disconnecting said radio signal (S_i+N_i) by
connecting at least one input of said one or more
amplifiers (100) to a reference potential (20).

23. A receiver (1) according to claim 22,
c h a r a c t e r i s e d in that said reference
potential is a resistance (20) through ground.
- 5 24. A receiver (2) according to any one of claims 20-21,
c h a r a c t e r i s e d in that said switching means
(100) is disconnecting said one or more amplifiers
(100,200) from said radio signal (S_i+N_i) by disconnecting
a power supply (500) from at least one amplifier of said
one or more amplifiers (100,200).
- 10 25. A receiver (1,2) according to any one of claims 20-24,
c h a r a c t e r i s e d in that the receiver (1,2)
further comprises:
more than one amplifiers (100+200) in a chain for
amplifying said received radio signal (S_i+N_i).
- 15 26. A receiver (1,2) according to any one of claims 20-25,
c h a r a c t e r i s e d in that said calibrating
signal is a noise power (kTBF) from said one or more
amplifiers (100,200) that comprises:
a known Boltzman constant (k);
20 a known bandwidth (B) of said noise power;
a known noise figure of said noise power;
a measured temperature (T) of said receiver.
- 25 27. A receiver (1,2) according to any one of claims 20-26,
c h a r a c t e r i s e d in that an output from the
last one of said one or more amplifiers (200) in a chain
is connected to an analog-digital-converter (400) for
converting analog signals into digital signals.
- 30 28. A receiver (1,2) according to claim 26,
c h a r a c t e r i s e d in that said gain (G) of said
received radio signal (S_i+N_i) is estimated from said
calibrating signal (N_a+N_i) including said noise power
(kTBF) when an output signal (S_{tot}) is measured at least
one output of said one or more amplifiers (100,200).

29. A receiver (1,2) according to any one of claims 20-27,
c h a r a c t e r i s e d in that said gain (G) of said
received radio signal (S_1+N_1) is estimated from said
calibrating signal (N_a+N_1) when an output signal (S_{tot})
5 is measured at least one output of said one or more
amplifiers (100,200).
30. A receiver (1,2) according to any one of claims 20-27,
c h a r a c t e r i s e d in that said gain (G) of said
received radio signal (S_1+N_1) is estimated from said
calibrating signal (N_a+N_1) when an output signal (S_{tot})
10 is measured after said analog-digital-converter (400).